



ART. 36060

Pneumatic pumps for oil

Modular pneumatic piston pump s. 650 for distributing oil and similar, R 5:1 - 18 l/min with NBR seals



FLUIDS

WASTE OIL | FRESH OIL

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING
WASTE OIL | FRESH OIL

Features	UM	Value
Flow rate	l/min	18
Ratio		5:1
Compatible fluids		oils, lubricants and similar
Suction tube upper body		aluminum
Suction tube		carbon steel
Air inlet connection		G 1/4" (f)
Fluid outlet connection		G 1/2" (f)
Air working pressure	bar	6 ÷ 8
Average air consumption	l/min	350
Noise level	dB	81
max deliverable oil viscosity	SAE	240
Bung adaptor		-
Suitable for drums or tanks		modular
Packing	N° - m ³	1 - 0,01
Weight	kg	4,7
Dimensions (A-B-C)	cm	34,5 - 27 - 4,2

RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2019 All rights reserved to RAASM S.p.A.